



WEIGUANG




TOTAL INGENIEROS S.A.C
VENTAS, PROYECTOS, SERVICIOS EN INGENIERIA Y SISTEMAS DE REFRIGERACION

NO. 4E300S-2022-A0

WEIGUANG
S.R.L. 100040 L. PIRELLA
GRUPPO 100040 L. PIRELLA
TOTAL WIGUANG S.R.L.

WEIGUANG®


SPECIFICATION 规格说明
HANGZHOU WEIGUANG ELECTRONIC CO.,LTD.




LABEL (铭牌):



WIRING DIAGRAM (接线图):



FLOW RATE CURVE (风量曲线):



UNIT 类型	Axial fan motor 外转子轴流风机
MOTOR 电机型式	Single phase motor with capacitor
MOTOR TYPE 电机型号	YWF4E-300S-92/35-G
VOLTAGE 额定电压 (V)	220
FREQUENCY 频率 (Hz)	60
INPUT POWER 输入功率 (W)	100
CURRENT 电流 (A)	0.46
SPEED 转速 (r/min)	1550
AIR FLOW 20Pa 风量 (m³/h)	2015
NOISE 噪音 (dBA)	61
CAPACITOR 电容 (μF/450V)	3
ROTATION 旋转方向	CW ,looking into the end-shield 顺时针, 从端盖端方向看
INSULATION CLASS 绝缘等级	F
MOTOR PROTECTION 电机保护	Thermocontact 150±5℃ 热保护器
TEMPERATURE RISE 温升	75K max 运行温升不超过75K
TYPE OF PROTECTION 防护等级	IP54
OPERATING TYPE 工作定额	S1 连续工作制
AMBIENT TEMPERATURE 适用环境温度	-30℃ +60℃
BEARINGS 轴承型式	Ball bearings 滚珠轴承
MOUNTING TYPE 安装方式	Horizontal or Vertical 垂直或水平安装
ELECTRICAL CONNECTION 电源线	Lead wire RV-90 4G 0.50mm², Length 100mm in terminal box connected 接线盒 (4芯0.5mm²线长100mm)
APPROVALS 认证标记	CCC、CE
NET WEIGHT/GROSS WEIGHT 净重/毛重	3.0/4.0kg
PACKING 包装	34*34*18cm

					DRN. BY	SIGN	DATE	TITLE
					CHD. BY			YWF4E-300S-92/35-G
					ENG. BY			PROJECTION
REV.	DESCRIPTION	APPROVED	DATE		APP. BY			A4 SCALE SHEET: of